



LNG Flowrate Measurement Using Laser Doppler Velocimetry (LDV)

A.Strzelecki, A. Ouerdani, Y. Lehot,
C. Windenberger, J.P. Vallet
CESAME- EXADEBIT


Acknowledgement

The research leading to the results discussed in this talk has received funding from the European Metrology Research Programme (EMRP). The EMRP is jointly funded by the EMRP participating countries within Euramet and the European Union.

LNG SUPPLY CHAIN



LNG tankers capacity varies between
95 000 m³ and 160 000 m³




LNG ENERGY SALES



Energy Transferred from the loading facilities to the LNG carrier or from the carrier to the unloading facilities

$$E = V_{LNG} \times D_{LNG} \times GCV_{LNG} - E_{\text{gas displaced}}$$



Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

3

LNG ENERGY SALES



Energy Transferred from the loading facilities to the LNG carrier or from the carrier to the unloading facilities

$$U[E_{LNG}; k=2]=0.76$$

GIIGNL LNG Custody Transfer Handbook 3rd Edition

$$E = V_{LNG} \times D_{LNG} \times GCV_{LNG} - E_{\text{gas displaced}}$$

□ Level Gauging & Calibration Table

(level gauges, calibration tables, correction tables, temperature probes distributed in the LNG tanks)

$$U[V_{LNG}; k=2]=0.21$$

Volume of LNG loaded or unloaded

□ In line flow measurement of LNG

- Coriolis Flowmeter
- Differential pressure Flowmeter
- Ultrasonic Flowmeter

} Lack of large scale calibration facilities for LNG


Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

4

JRP METROLOGY FOR LNG [2010-2013] Project aims and objectives



contribute to a significant reduction of uncertainty in the determination of transferred energy in LNG custody transfer processes



Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

5





OUTLINE

- Introduction
- Technical feasibility
- Experimental Means
- Results & discussion
- Conclusion & perspectives

Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

6

Principle of the volume flow rate measurement with a LDV




Measurement volume

Δi interfringe

Doppler Frequency f_D

$$\Delta i = \frac{\lambda_0}{2 \cdot \sin\left(\frac{\theta}{2}\right)}$$

$$U = \Delta i \cdot f_D$$



$$Q_v = 2\pi \int_0^R U(r) r dr$$

The volume flow rate measurement Q_v based upon the measurement of velocity profiles at a nozzle exit plane is directly traced back to SI units of Length and Time

Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

7

Studying technical feasibility of LNG Flowrate measurement using LDV



The flowrate measurements using a LDV technique is not new

PTB (Germany) developed an Optical Primary National standard based on LDV measurement for Natural Gas of High Pressure (50 bar). Accuracy $U(Q_v; k=2) = 0.13\%$ [$\rightarrow 0.10\%$]

D. Vieth, H.M Hinze, B. Mickan, R. Kramer, H. Müller, & V. Strunck, IGRC Conférence 2008, Paris

WHAT is Challenging in this study?

- ❑ handle the cryogenic conditions with the LDV system & no flashing
- ❑ design the optical access for the LDV at low temperature (-266°C)
(avoid the icing, reduce the stresses in the optical windows)
- ❑ develop an adapted & clean seeding for LDV Measurements
(particles naturally present in the LNG or injected)
- ❑ accuracy less than 0.20 %

Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

8

Studying technical feasibility of LNG Flowrate measurement using LDV




Conditions for In-line flow measurements of LNG

- Pipe diameter DN 900 (36'')
- Temperature = - 166°C
- Pressure < 10 bar
- Flowrate of LNG = 5000 to 15 000 m³/h
- Mean pipe velocity = 2 to 7 m /s
- Pipe Reynolds number = 9×10^6 to 3×10^7
- Extended accuracy better than 0.20 %

Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

9

LNG Measurement system: technical feasibility




□ Flow conditions in the pipe

➢ LNG Unloading conditions
(P,T,Qv, D)

➢ Fluid= LNG;

P<10 Bar ;T= - 166°C




□ Measurement System

- Seeding unit
- Conditioning the flow with a convergent (optimization → Flow simulation)
- Local velocity measurement by means of the LDV
- Vacuum insulated to avoid icing of the optical windows
- Optical access (temperature gradient) for laser beams & flow visualization

Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands


10

LNG MEASUREMENT SYSTEM




- ❑ DN 80
- ❑ Beta Ratio = 0.5
- ❑ Total length 12 D
- ❑ Vacuum insulated 10^{-3} - 10^{-5} mb
- ❑ Quartz windows for LN2 or LNG measurements (- 160°C)
- ❑ Convergent & Nozzle optimisation for the Reynolds Number Range
- ❑ Use the Delta P for flowrate measurement

CESAME EXADEBIT FLOW LOOP




- **Flow rate** : $Q_m = 4.10^{-4}$ to 30 kg/s ,
 $Q_v = 1$ à 80 000 m³/h
 (normal conditions)
- **Pressure** : 1 to 45 bar
 (depending on the flowrate)
- **Reference flowrate uncertainties** :
 0.20 to 0.25 % depending on the
 flowrate

LASER DOPPLER VELOCIMETRY



- LDV DANTEC
- Laser power = 40 mW
- $\lambda = 532$ nm (green light)
- Back scattering mode
- Focal length = 160 mm
- Measurement volume $l=0.05$ & $L=0.4$ mm
- Interfringe spacing = $2.2 \mu\text{m}$



Measurement volume

Δi interfringe

Doppler Frequency f_D

$$\Delta i = \frac{\lambda_0}{2 \cdot \sin\left(\frac{\theta}{2}\right)}$$

$$U = \Delta i \cdot f_D$$

Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

13



AIR BASED EXPERIMENTS: MEASUREMENT CONDITIONS

- Fluid = Compressed AIR
- Pipe Diameter = 0.080 m

Pressure (abs.) [Bar]	Throat Velocity [m/s]	Pipe Reynolds Number
1.5	5; 20; 57	1.0E+4 to 1.1E+5
5	5; 20; 57	3.3E+4 to 3.8E+5
10	5; 20; 57	6.5E+4 to 7.2E+5

AIR BASED EXPERIMENTS WITH REYNOLD NUMBER SIMULATING LNG CONDITIONS

□ Pressure 1 to 10 bar; Reynolds Number = 10^4 to 10^6




Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

15

AIR BASED EXPERIMENTS WITH REYNOLD NUMBER SIMULATING LNG CONDITIONS

P= 5 bar ; Influence of the Throat Velocity [5, 20 & 57 m/s] on the Mean & RMS Velocity 16 mm downstream the throat




Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

16

AIR BASED EXPERIMENTS WITH REYNOLD NUMBER SIMULATING LNG CONDITIONS

**Throat Velocity= 20 m/s; Influence of the Pressure [1.5, 5 & 10 bar]
on the Mean & RMS Velocity 16 mm downstream the throat**



Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

17

FLOWRATE MEASUREMENT WITH THE CRYOGENIC MEASUREMENT SYSTEM

$$Q_v = \pi R^2 \bar{v} = \pi R^2 \frac{v_{axis}}{A(Re_d)} \quad \text{with} \quad \frac{v_{axis}}{\bar{v}} = A(Re_d) \quad \& \quad Re_d = \frac{\bar{v} d \rho}{\mu} = \frac{4 Q_m}{\pi \mu d}$$

v_{axis} Axis Mean Velocity 16 mm downstream the throat
 R Throat Radius
 \bar{v} Mean Velocity at the throat
 Re_d Ranging from 5 E+04 to 1.5 E+06 $\bar{A}=1.01$

FLOWRATE UNCERTAINTY $U_{relative}[Q_v ; k=2] = 0.6 \%$

*Needs to Improve the accuracy of the total flowrate measurement
[$Q_{total} = Q_{Air\ flow} + Q_{V\ seeding}$] & the uncertainty $U(V_{LDV})$*

Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

18

IMPROVEMENT OF THE FLOWRATE ACCURACY WITH THE CRYOGENIC MEASUREMENT SYSTEM

- ❑ needs to reduce ΔA (shift on $A[R_D]$)
- ❑ reduce the Reynolds Number Influence



target ➡ LNG Flowrate uncertainty < 0.2 %



- ❑ improvement of the design of the measurement system
- ❑ the V_{axis} measures closer to the throat outlet
- ❑ industrial conditions (Tanker Unloading) $Re_d = 1E+07$
- ❑ confirmed by means of Flow simulations

Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

19

LNG Flowrate measurement using LDV

- ❑ Pipe diameter DN 900 (36'')
- ❑ Length = 6 - 8 D
- ❑ Pressure < 10 bar
- ❑ Flowrate of LNG = 5000 to 15 000 m³/h
- ❑ Pressure Loss < 500 mb ($K = 0.26$)
- ❑ Mean pipe velocity = 2 to 7 m /s
- ❑ Pipe Reynolds number = 9×10^6 to 3×10^7
- ❑ With a Reynolds Number = 10^7 an accuracy better than 0.20 % seems realistic
- ❑ measurement of the flowrate with the Delta P



Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

20

CONCLUSION

- ❑ feasibility to realize a measurement system to measure the flowrate of LNG
- ❑ achieved expanded Uncertainty 0.6% on the volume flow rate with the LDV measurement system (air based experiments)
- ❑ proposal to improve the accuracy
- ❑ objective of an accuracy on the volume flowrate better than 0.2% seems realistic



Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

21

PERSPECTIVES

- ❑ improve the design of the LDV cryogenic Measurement system
- ❑ validation of the measurement system in cryogenic conditions (Liquid Nitrogen and LNG)
(LN2 @NIST- LNG@VSL & LNG Terminal GDF Suez/ELENGY)
- ❑ assessment of an accuracy better than 0.2% to measure LNG flowrates



THANKS FOR YOUR ATTENTION

Metrology for LNG conference, 17-18th October 2013, Delft, the Netherlands

22